SPECIFICATIONS

SUPRA 850 Mt°

With an unmatched reputation for performance and reliability, SUPRA is a range that has always known how to anticipate and evolve with market and customer needs.

Today, we are associating our worldleading multitemperature technology to make the latest SUPRA range available for your multitemperature applications too.

This multitemperature range brings you all the benefits of new technological developments, as well as unparallelled low levels of noise for operation in noise-sensitive areas.

► Total flexibility for multi-product deliveries with a new generation of ultra-slim evaporators that can be adapted to any configuration requirement

- Exceptional performance characteristics for enhanced product protection even with frequent dooropenings
- ► Exceptional reliability of components field-tested for years with the market-leading SUPRA range
- ► Improved service accessibility that reduces maintenance time and saves
- ► Greater ease of use with EasyCOLD® microprocessor control.



Condenser

Dimensions

1823 x 856 x 644 mm

Required box opening

90 x 90 mm

Weight

T Model: 446 kg S Model: 443 kg

X Model: 448 kg

Refrigeration capacity

 $-20 \, ^{\circ}\text{C} / + 30 \, ^{\circ}\text{C}$: up to 4400 W



Microprocessor cab command:

- proven reliability
- easy to use
- servicing functions

T model

HFC R404A refrigerant

719 cc Tri-Vortex diesel engine

05K4 4-cylinder compressor

Standby motor

Remote plug

Low-noise sound control kit

Automatic hot gas / electric heating and

defrost system

Manual defrost

Directly accessible oil gauge

Moisture indicator

Two sight glasses to monitor refrigerant

Dry air, fuel and oil filters

50-amp 12V alternator

220 V generator

Accessory package (electric fuel pump, fuel lines, battery cables)

EasyCOLD® Microprocessor control system

S model

Version without low-noise sound control

X model Silent

Ultra-low noise system with an identification and elimination of noise at its source

Accessories

Battery

Battery box

Fuel tank 90 or 200 l

Automatic phase reverser 400/3/50Hz

Control panel & cable extension


Door switch

Fuel heater

Total flexibility in multi-product deliveries with the new configurations of the SUPRA 850 Mt° available with its ultra-slim evaporators range. Other configurations are available upon request.











Extension kit



Specifications are subject to change without notice.



500 Carrier service stations in Europe, Russia, Middle East and Africa



Carrier Transicold Europe S.C.S. 10, boulevard de l'Oise F-95031 Cergy Pontoise Cedex Phone: +33 (0)1 34 43 48 00 Fax: +33 (0)1 34 43 48 48 www.carrier-transicold-europe.com

© Carrier Corporation - Carrier Transicold Europe S.C.S. au capital de 16 090 700 euros - R.C.S. Pontoise B 410 041 776 - Code APE 518M VAT: FR52410041776 - The information contained in this document is not contractually binding, and may not be reproduced without prior approval. Printed in France (01-05) 62-61054-23