SPECIFICATIONS

CMJKPMS072PMS877(01/05) 62-61055-22

With an unmatched reputation for performance and reliability, SUPRA is a range that has always known how to anticipate and evolve with market and customer needs.

Today, we are associating our worldleading multitemperature technology to make the latest SUPRA range available for your multitemperature applications too.

This multitemperature range brings you all the benefits of new technological developments, as well as unparallelled low levels of noise for operation in noisesensitive areas.

Total flexibility for multi-product deliveries with a new generation of ultraslim evaporators that can be adapted to any configuration requirement

T model

Standby motor

Remote plug

defrost system

Manual defrost

level

Moisture indicator

HFC R404A refrigerant

1,1 litre Tri-Vortex diesel engine

05G 6-cylinder compressor

Low-noise sound control kit

Directly accessible oil gauge

Dry air, fuel and oil filters

50-amp 12V alternator

Automatic hot gas / electric heating and

Two sight glasses to monitor refrigerant



Condenser Dimensions

1995 x 940 x 699 mm Required box opening

100 x 100 mm

Weight T Model: 569 kg S Model: 566 kg X Model: 573 kg

\$

Refrigeration capacity

- 20 °C / + 30 °C: up to 6200 W


Microprocessor cab command: proven reliability

easy to use



Total flexibility in multi-product deliveries with the new configurations of the SUPRA 950 Mt° available with its ultra-slim evaporators range. Other configurations are available upon request.

4000 m³/h 1200 2500 m3/h m³/h 450 700







500 Carrier service stations in Europe, Russia, Middle East and Africa



Carrier A United Technologies Company

Carrier Transicold Europe S.C.S. . 10, boulevard de l'Oise F-95031 Cergy Pontoise Cedex Phone: +33 (0)1 34 43 48 00 Fax: +33 (0)1 34 43 48 48 www.carrier-transicold-europe.com

SUPRA 950 Mt°

Exceptional performance

characteristics for enhanced product protection even with frequent dooropenings

Exceptional reliability of components field-tested for years with the marketleading SUPRA range

Improved service accessibility that reduces maintenance time and saves costs

Greater ease of use with EasyCOLD® microprocessor control

Unheard-of sound levels reduced up to 4 decibels with the ultra-low noise kit.

220 V generator

Accessory package (electric fuel pump, fuel lines, battery cables) EasyCOLD® Microprocessor control system

S model

Version without low-noise sound control kit

X model Silent

Ultra-low noise system with an identification and elimination of noise at its source

Accessories

450

2500 m³/h

1200 m³/h

2500 m3/h

2300 2300

m³/h m³/h

1200 m³/h

Batterv Battery box Fuel tank 90 or 200 l Automatic phase reverser 400/3/50Hz Control panel & cable extension Door switch Bypass oil filter Engine oil drain extension Fuel heater

2500 m³/h 2500 m3/h





1200 m³/h 2 1200 m³/h 2500 m3/h

Extension kit



Specifications are subject to change without notice.

© Carrier Corporation - Carrier Transicold Europe S.C.S. au capital de 16 090 700 euros - R.C.S. Pontoise B 410 041 776 - Code APE 518M VAT: FR52410041776 - The information contained in this document is not contractually binding, and may not be reproduced without prior approval. Printed in France (01-05) 62-61055-22