PRODUCT SPECIFICATIONS

XARIOS 600 Mt°

XARIOS 600 Mt° is a new, high capacity multi-temperature unit specifically designed for urban distribution vehicles with box volumes up to 30m³.

► A modular concept for application versatility

- ► Totally reversible from 20 °C to
- + 10 °C, for operating flexibility
- ► Rapid installation and easy servicing that contribute to reduced life cycle cost
- Unrivalled temperature recovery for urban distribution
- ► Choice of evaporator for maximum load space
- Innovations that respect the environment
- ➤ Microprocessor control and cab command make operation easier and safer.





New unique multi-function 4-digit cab command with Full APi Control Logic®, developed exclusively for the XARIOS multitemperature range.

Condenser

Dimensions

1367 x 514 x 498 mm

Weight

of 30m3.

Road / Standby: 152 kg

Road: 88 kg

Refrigeration capacity

- 20 °C / + 30 °C: up to 3090 W

Heating capacity

 $+ 20 \, ^{\circ}\text{C} \, / \, -18 \, ^{\circ}\text{C}$: up to $4 \, 300 \, \text{W}$

T model

Refrigerant HFC R404A Standby compressor Carrier 06VM307 High capacity hot gas heating and defrost Road or Road & Standby operation

400/3/50

Operation on 12VDC and 24VDC vehicles

Equipment

Road compressor: TM16
Road compressor mounting kit

Accessories

Door switch

A range of 3 powerful slimline evaporators and 1 vertical evaporator, ensure maximum airflow


different configurations according to your specific application up to a total maximum volume

capacity and exceptional loading space. These can be adapted to an extensive number of

Water drain heater



Maximum volume up to 12 m³



MXV 850 evaporator

Dimensions: 853 x 159 x 619 mm

Weight: 17 kg Airflow: 770 m³/h





Maximum volume up to 20 m³

MXL 1100 evaporator

Dimensions: 1106 x 614 x 194 mm

Weight: 29 kg Airflow: 1500 m³/h





Maximum volume up to 12 m³

MXS 850 evaporator

Dimensions: 853 x 608 x 172 mm

Weight: 19 kg Airflow: 830 m³/h





Up to 2,60 m

MXS 600 evaporator

Dimensions: 603 x 548 x 172 mm

Weight: 15 kg Airflow: 650 m³/h



Specifications are subject to change without notice.



500 Carrier service stations in Europe, Russia, Middle East and Africa



Carrier

A United Technologies Company

Carrier Transicold Europe S.A.S. 10, boulevard de l'Oise F-95031 Cergy Pontoise Cedex Phone: +33 (0)1 34 43 48 00 Fax: +33 (0)1 34 43 48 www.carrier-transicold-europe.com

© Carrier Corporation – Carrier Transicold Europe S.A.S. au capital de 16 090 700 euros – R.C.S. Pontoise B 410 041 776 – Code APE 518M VAT: FR52410041776 – The information contained in this document is not contractually binding, and may not be reproduced without prior approval. Printed in France (04-04) 62-61083-20